



Clear Sealers: COBBLE COAT H2O Wet, 235-1g, 235-5g

Technical Data Sheet

COBBLE COAT H2O Wet

Wet-Look Appearance, Semi Gloss Finish

Characteristics & Technical Data

% Solids by Weight:	40%
QUV (ASTM D G-53):	1000 hours > 50% color retention
WT./Gal:	8.5
Coverage:	200 to 300 SqFt/Gal @ 2mil DFT
VOCs:	<250 G/L

1. Manufacturer

SurfaceLogix – a Reliance Supply Company
1880 NW 18th Street
Pompano Beach, FL 33069

Phone: 954.971.9111
Fax: 954.971.6623
Email: support@surfacelogix.net
Website: www.surfacelogix.net

2. Product Description

Cobble Coat H2O Wet is the newest technology in waterborne protection for concrete brick pavers. Cobble Coat H2O Wet is a wet look waterborne sealer designed to provide the dark wet look without the harsh smell or harmful effects of solvent, while still providing excellent UV light protection. Cobble Coat H2O Wet provides stain resistance and is specially designed for DIY use. One coat gives a dark wet look on most surfaces, two coats provide a sheen.

3. Applications

Use Cobble Coat H2O Wet on driveways, patios, pool decks, parking lots, walkways, etc. constructed of:

Concrete Pavers Only

Cobble Coat H2O Wet is not recommended for pavers installed over a solid surface or on surfaces where moist moisture is unable to dissipate.

4. Properties & Special Features

- Eco friendly, Biobased & emits low VOC's
- Easy to apply
- Helps stabilize joint sand
- Helps inhibit algae, weeds and ant hills
- Single Component, so no mixing or waste
- Natural biodegradability helps prevent sealer buildup and resists hazing

5. Directions

Before You Begin: Surfaces must be clean and free of any contaminants before sealing. Cobble Coat H2O Wet's performance is directly related to how thoroughly the surfaced is prepared. All grease, oil, and potential contaminates must be removed. Do not apply when the temperature of the air or the surface to be coated is below 50°F. Testing on your surface is always recommended to ensure desired results.

Surface Preparation: Brick pavers should be installed a minimum of 28 days before sealing. Read label instructions carefully. Cobble Clean, Cobble Prep & Cobble Oxhide may be used for specific cleaning situations.

Mixing Instructions: Stir product, some separation may occur and will easily mix in.

Application

Roller: Apply with a 3/8" to 3/4" nap roller cover. Avoid over rolling. Always maintain a wet edge. Do not pool or over apply.

Airless Sprayer: Spray by overlapping each pass. Always apply in an even film deposit and maintain a working wet line.

Continued ->

Clear Sealers: COBBLE COAT H2O Wet, 235-1g, 235-5g

Technical Data Sheet

COBBLE COAT H2O Wet



5. Directions (Continued)

On Bare Surface: One and sometimes two thin coats (2 dry mils) provide the best results on uncoated surfaces.
Previously Sealed: One coat is recommended. Do not apply Cobble Coat H2O Wet more frequently than every 12 months to avoid a build up of sealer.

6. Packaging

Size	Package	Per Case	Units / Pallet
1 gallon	Pail	4	148
5 gallon	Pail	N/A	36

9 pounds per 1 gallon pail, 45 pounds per 5 gallon pail

7. Coverage

1 gallon covers 200 to 300 square feet per coat. Coverage will depend on surface porosity, joint width, and method of application. Second coat will take slightly less product.

8. Curing Information

Dry To Touch: 2 Hour *

Recoat: 8 Hours

Full Cure: 48 to 72 Hours

*Cobble Coat H2O Wet's unique curing mechanism can result in longer than normal tack times if over applied or applied to dense substrates.

9. Storage & Shelf Life

Product must be kept in its original, unopened and tightly sealed container. Store in a dry and well ventilated place with controlled temperature (50°F to 90°F). Keep sheltered from weather and direct sunlight. In proper storage conditions, the product's shelf life is 12 months following production (see date on packaging). Store product in original container and close lid tightly after each use.

10. Maintenance

Cobble Clean is recommended for routine cleaning. Follow Cobble Clean instructions for dilution ratios.

11. Shipping

Land and sea: Not Regulated

Packing Group: III

Flash Point: Not Applicable

12. Clean Up

Clean sprayer and application tools with water.

13. Health Hazard Information

Eye Contact: Wear Eye Protection. May irritate eyes. If in eyes, flush with water for at least 15 minutes.

Inhalation: Use a NIOSH approved respirator.

Ingestion: If swallowed, DO NOT induce vomiting. Seek medical attention.

Skin: Avoid prolonged contact with skin.

Use with adequate ventilation.

Coated surfaces may become slippery. SurfaceLogix Non-skid Additive should be incorporated in this situation. However, it is the sole responsibility of the applicator to determine whether a non-skid additive is appropriate for the job.

14. Technical Support

For friendly, knowledgeable and courteous technical support please call 954.971.9111.

You may also reach us by sending a query from our website at www.surfacelogix.net.

15. Disclaimer

All SurfaceLogix products are manufactured with the finest raw materials. It is the applicator's responsibility to determine the appropriate use of the product.

All recommendations and suggestions are made without guarantee, since conditions of use are beyond our control.