

Technical Data Sheet

GATOR SKIN REPELLENT

Enhanced Appearance, No Sheen



Characteristics & Technical Data

| | |
|---------------------|----------------------|
| % active by Weight: | 5% |
| WT./Gal: | 6.6 |
| Coverage: | 200 to 2000 SqFt/Gal |
| VOCs: | >600 G/L |

4. Properties & Special Features

- Easy to apply
- Breathable
- Keeps natural appearance
- inorganic
- protects the substrate by deeply penetrating

5. Directions

Before You Begin: Surfaces must be clean, dry and free of any contaminants before sealing. Gator Skin Repellent performance is directly related to how thoroughly the surfaced is prepared. All grease, oil and potential contaminants must be removed. Do not apply when the temperature of the air or the surface to be coated is below 50° F. Testing on your surface is always recommended to ensure desired results.

Surface Preparation: Concrete should cure a minimum of 28 days before sealing. Read label instructions carefully. Cobble Clean, Cobble Prep and Cobble Oxhide may be used for specific cleaning situations.

Mixing Instructions: Stir product.

Application

Roller: Apply with a lambs wool or microfiber cloth, working the material into the surface.

Airless Sprayer: Spray by overlapping each pass. Always apply in an even film deposit and maintain a working wet line. Remove any excess material after 3-5 minutes.

On Bare Surface: Apply to the surface and allow to penetrate for 3-5 minutes, remove any excess. Do not allow any excess or pooling to dry on the surface.

Over Previously Sealed: Film forming sealers will need to be stripped prior to application. Gator Skin Repellent may be applied over non film forming sealers provided the prior application is sufficiently worn away.

1. Manufacturer

SurfaceLogix – a Reliance Supply Company
1880 NW 18th Street
Pompano Beach, FL 33069

Phone: 954.971.9111

Fax: 954.971.6623

Email: support@surfacelogix.net

www.surfacelogix.net

2. Product Description

Gator Skin is an inorganic silicone penetrating protectant. Its inorganic silicone chemistry means that it is not broken down by natural elements. By deeply penetrating into the substrate it offers years of internal protection. Its breathable nature means it will not trap moisture and will prevent water penetration into the substrate protecting it from weather.

3. Applications

Use Gator Skin on any porous material that needs protections for the elements such as:

Natural Stone • Bricks • Wood • Concrete



surface logix

CHEMISTRY THAT PROTECTS YOUR WORLD

Clear Sealers: **GATOR SKIN REPELLENT**, 233-1g, 233-5g

Technical Data Sheet

GATOR SKIN REPELLENT

Deeply Penetrating Internal Protectant

5. Directions (Continued)

Note: Excess or puddled sealer must be removed from the surface before it dries. This timing will depend on temperature and exposure.

6. Packaging

| Size | Package | Per Case | Units / Pallet |
|----------|---------|----------|----------------|
| 1 gallon | Pail | 4 | 148 |
| 5 gallon | Pail | N/A | 36 |

7 pounds per 1 gallon pail, 35 pounds per 5 gallon pail

7. Coverage

1 gallon covers 200 to 2000 square feet per coat. Coverage will depend on surface porosity, joint width, and method of application.

8. Curing Information

Dry To Touch: After excess is removed, surface should feel dry.

Recoat: 2 Hours

Full Cure: 48 —72 Hours

9. Storage & Shelf Life

Product must be kept in its original and tightly sealed container. Store in a dry and well ventilated place with controlled temperature (50°F to 90°F). Keep sheltered from weather and direct sunlight. In proper storage conditions, the product's shelf life is 24 months following production (see date on packaging). Store product in original container and close lid tightly after each use.

10. Maintenance

Cobble Clean is recommended for routine cleaning. Follow Cobble Clean instructions for dilution ratios.

11. Shipping

Land and sea: Not Regulated

Packing Group: III

Flash Point: 52-53 C

12. Clean Up

Clean sprayer and tools with Odorless Mineral Spirits immediately after use.

13. Health Hazard Information

Eye Contact: Wear Eye Protection. May irritate eyes. If in eyes, flush with water for at least 15 minutes.

Inhalation: Use a NIOSH approved respirator.

Ingestion: If swallowed, DO NOT induce vomiting. Seek medical attention.

Skin: Avoid prolonged contact with skin.

Use with adequate ventilation. May be used interior or exterior application.

Any surface may become more slippery when a coating is applied. In testing, Gator Skin Repellent increased the coefficient of friction on many substrates IE did not make the surface more slippery.

14. Technical Support

For friendly, knowledgeable and courteous technical support please call 954.971.9111.

You may also reach us by sending a query from our website at www.surfacelogix.net.

15. Disclaimer

All SurfaceLogix products are manufactured with the finest raw materials. It is the applicator's responsibility to determine the appropriate use of the product.

All recommendations and suggestions are made without guarantee, since conditions of use are beyond our control.